DO NOT MEASURE DRAWING . IF IN DOUBT PLEASE ASK.



All dimensions are in mm unless specified			
TITLE	HYDRO–PNEUMATIC INTENSIFIER DOUBLE ACTING		
MODEL	6110–220		
INT. RATIO	1:28	PROJECTION 3rd ANGLE	
OIL OUTPUT	200cc		
		MOUNTING	AS PER DRAWING
		RATED PR.	7 kg/cm²
SCALE	NTS	TEST PR.	10 kg/cm²
DRN	RBP	11/01/16	
CHKD	RBP	11/01/16	
APPD	RBP	11/01/16	

Unspecified m/c deviations (med to IS 2102)

Linear–Length or Diameter		
Over	Upto & inc.	TOL
–	6	±0.1
6	30	±0.2
30	120	±0.3
120	315	±0.5
315	1000	±0.8
1000	2000	±1.2

Length of shorter side of angle		
Over	Upto & inc.	TOL
–	6	±1°
6	30	±30'
30	120	±20'
120	315	±10'

PRECISION ENGINEERING ACCESSORIES

PEENYA BANGALORE

Surface Finish	Ra Value–μ	Roughness No.
▽▽▽▽	0.025	N1
	0.05	N2
	0.1	N3
▽▽▽	0.2	N4
	0.4	N5
	0.8	N6
▽▽	1.6	N7
	3.2	N8
	6.3	N9
▽	12.5	N10
	25	N11
~	50	N12