


Technical drawing of a 200L stainless steel tank, showing top and side views with dimensions and features.

Top View:

- Overall diameter: $\varnothing 61$
- Inner diameter: $\varnothing 25 \text{ f7}$
- Two mounting holes: $M6 \times 1, 15 \text{ dp}$ (2 Nos on 40PCD)
- 1/8" BSP AIR BREATHER

Side View:

- Overall height: 85
- Top flange height: 28
- Top flange diameter: $\varnothing 25 \text{ f7}$
- Bottom flange diameter: $\varnothing 13$
- Bottom flange height: 2
- 1/4" BSP

All dimensions are in mm unless specified					Unspecified m/c deviations (ref to IS 2102)	
TITLE	HYDRAULIC HOLLOW PISTON CYLINDER SINGLE ACTING SPRING RETURN				Line-dim	Depth or Diameter
MODEL	4610-111				Over	±0.1
BORE SIZE	φ40	PROJECTION		AS PER DRAWING	Over	±0.1
P.R SIZE	φ25	3rd ANGLE			6	±0.2
STROKE	10	MOUNTING			30	±0.3
					120	±0.5
					180	±0.5
					315	±0.8
					1000	±1.2
					2000	±1.2
SCALE	NTS	MINIMUM WORKING PRESSURE	5 kg/cm ²		Over	±0.1
		MAXIMUM WORKING PRESSURE	210 kg/cm ²		6	±0.1
D/N	R/P				30	±0.07
CHKD	R/S				120	±0.20
APPD	R/S				350	±0.20
					120	±1.0
					315	±1.0
PRECISION ENGINEERING ACCESSORIES					Up to	±0.1
PRENTA BANGALORE					± Inc.	±0.1