



DO NOT MEASURE DRAWING . IF IN DOUBT PLEASE ASK.



Surface Finish	50	25	12.5	6.3	3.2	1.6	0.8	0.4	0.2	0.1	0.05	0.025	N1	N2	N3	N4	N5	N6	N7	N8	N9	N10	N11	N12
Ra Value—μ	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Roughness No.	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

All dimensions are in mm unless specified					Unspecified m/c deviations (med to IS 2102)		
TITLE		HYDRAULIC ROTARY COUPLING			Linear—Length or Diameter		
MODEL		510-266			Over	Upto & inc.	TOL
No. OF PORTS	IN	6	PROJECTION 3rd ANGLE		—	6	±0.1
	OUT	6			6	30	±0.2
					30	120	±0.3
					120	315	±0.5
PORT SIZE		1/4" BSP		315	1000	±0.8	
MAX. RPM		50		MIN. WORKING PR.		10 kg/cm <sup>2</sup>	
SCALE		NTS		MAX. WORKING PR.		210 kg/cm <sup>2</sup>	
DRN	RBP	15/12/15	<div>PRECISION ENGINEERING ACCESSORIES</div> <div>PEENYA                      BANGALORE</div>				
CHKD	RBP	15/12/15					
APPD	RBP	15/12/15					
					Over	Upto & inc.	TOL
					—	6	±1°
					6	30	±30°
					30	120	±20°
					120	315	±10°